

# Interplay between discretization and algebraic computation in adaptive numerical solution of elliptic PDE problems

Mario Arioli\*, Jörg Liesen\*\*, Agnieszka Międlar\*\*\*, and Zdeněk Strakoš†

Received ..., revised ..., accepted ...

Published online ...

**Key words** adaptive finite element methods, boundary value problems, eigenvalue problems, a posteriori error analysis, linear algebraic solvers, balancing of errors, stopping criteria  
**MSC (2000)** 65F10, 65F15, 65N22, 65N25, 65N30

The Adaptive Finite Element Method (AFEM) for approximating solutions of PDE boundary value and eigenvalue problems is a numerical scheme that automatically and iteratively adapts the finite element space until a sufficiently accurate approximate solution is found. The adaptation process is based on a posteriori error estimators, and at each step of this process an algebraic problem (linear or nonlinear algebraic system or eigenvalue problem) has to be solved. In practical computations the solution of the algebraic problem cannot be obtained exactly. As a consequence, the algebraic error should be incorporated in the context of the AFEM and its a posteriori error estimators. The goal of this paper is to survey some existing approaches in the AFEM context that consider the interplay between the finite element discretization and the algebraic computation. We believe that a better understanding of this interplay is of great importance for the future development in the area of numerically solving large-scale real-world motivated problems.

Copyright line will be provided by the publisher

## 1 Introduction

The finite element method (FEM) is widely used in order to discretize variational formulations of partial differential equations representing boundary value or eigenvalue problems. In this method an approximation to the exact PDE solution is found as a linear combination of basis vectors (functions) from a finite dimensional function space, called the *finite element space*. The coefficients in this linear combination are determined by solving a linear algebraic problem (linear algebraic system or algebraic eigenvalue problem). The construction of the finite element space is based on a mesh that discretizes the domain on which the PDE is formulated.

---

\* mario.arioli@stfc.ac.uk, Rutherford Appleton Laboratory, Chilton Didcot Oxfordshire, UK OX11 0QX

\*\* liesen@math.tu-berlin.de, Institute of Mathematics, Technical University of Berlin, Straße des 17. Juni 136, 10623 Berlin, Germany

\*\*\* miedlar@math.tu-berlin.de, Institute of Mathematics, Technical University of Berlin, Straße des 17. Juni 136, 10623 Berlin, Germany

† strakos@karlin.mff.cuni.cz, Faculty of Mathematics and Physics, Charles University in Prague, Sokolovská 83, 186 75 Praha 8, Czech Republic

Copyright line will be provided by the publisher

The basis functions typically have a local support consisting of several mesh elements. Usually, a finer mesh leads to a better approximation. However, there is a trade-off: finer meshes mean more finite element basis functions, hence larger algebraic problems, and consequently a higher computational effort for determining the approximate solution.

To balance accuracy of numerical approximation and cost of computation one can use the following idea: start with a coarse mesh, compute an approximate solution, refine the mesh only in regions where this approximation is not good enough, and then compute a new approximation using the refined mesh. What we have just described is one iteration of the *Adaptive Finite Element Method (AFEM)*, which starts with setting the mathematical model and its initial approximation, and which can schematically be written as follows:



Here “SOLVE” means solving the linear algebraic problem (linear algebraic system or eigenvalue problem) and “ESTIMATE” means the *local a posteriori* estimation of the error between the exact solution and its numerical approximation. The steps “MARK” and “REFINE” refer to the actual refinement of the mesh; they are not in the focus of this paper. In short, the AFEM can be described as a numerical scheme that automatically and iteratively adapts the finite element space until a sufficiently accurate approximate solution is found.

The AFEM is no new development. This is documented, e.g., by a special issue of *Computing* devoted to “adaptive techniques” published in 1995, where Hackbusch wrote in the Editorial:

Adaptivity is a further development. Instead of solving problems with a discretization of very high dimension, it is more reasonable to obtain the same solution quality by a lower dimensional but adapted discretization. Adaptivity has created a new paradigm in mathematical computation. In traditional numerical mathematics, the fields “discretization” (e.g., FEM), its “numerical analysis” (e.g., error estimates), and “solution algorithms” (e.g., solvers for linear systems) are well separated. Adaptive techniques, however, require a combination of all three. For example, the error estimation has become a part of the algorithm. The concrete discretization is now an outgrowth of the algorithm.

The special issue of *Computing* contains recommendable contributions, among them the paper of Becker, Johnson and Rannacher [22], which affected further development related, in particular, to multigrid finite element methods. In the Introduction, which can be considered a rigorous formulation of the new research program, the authors write:

[F]or large size problems, in particular in three dimensions, direct methods are too work-intensive and only iterative methods such as multigrid methods or preconditioned conjugate gradient type methods may be used. ... Usually, ad hoc stopping criteria are used, e.g. requiring an initial (algebraic) residual to be reduced by a certain ad hoc factor, but these criteria have no clear connection to the actual error in the corresponding approximate solution, which is the quantity of interest. This leaves the user of iterative solutions methods in a serious dilemma: With no objective stopping criterion available, one has either to continue the iterations until the discrete solution error is practically “zero”, which increases the computational

cost with possibly no gain in the overall precision, or take the risk of stopping the iterations prematurely. In the first case there would be a loss of efficiency and in the second a loss of reliability. ... A solution to this problem can only be obtained by combining aspects of the underlying partial differential equations and the corresponding finite element discretization with aspects of the iterative discrete solution algorithm. A “pure” numerical linear algebra point of view, for instance based on the condition number of the stiffness matrix, does not appear to be able to lead to a balance of discretization and solution errors.

It is remarkable that only a relatively small percentage of the research devoted to adaptive finite element methods has adopted this point of view. In fact, in the vast majority of publications on the AFEM (and on the FEM in general) it is assumed that the step “SOLVE” is performed *exactly*. Moreover, in almost all publications considering inexact solution of the algebraic problem, the inexactness is identified with iterative methods and their premature stopping, while it is assumed that the algebraic computations are performed in exact arithmetic. As a consequence, in the majority of publications on the AFEM it is assumed that direct solvers are “exact” (irrespective of the numerical properties of the problems to be solved), and maximum attainable accuracy as well as delay of convergence of iterative methods are excluded from consideration. These assumptions, however, cannot be satisfied in practical computations; see, e.g. [122]. Their violation can lead to discrepancies between proven statements for arbitrary error tolerance on the one hand, and computational results on the other; see, e.g. Theorem 3.11 and experimental results presented in [96].

We believe that a better understanding of the interplay between discretization and algebraic computation (including rounding errors) in the adaptive numerical solution of PDEs is of great importance for the future development in the area of numerically solving large-scale real-world problems. Our main intention in this paper is to survey some approaches that consider this interplay. To illustrate the main results and algorithms we use the setting of standard *linear, elliptic and selfadjoint* model problems. We state these problems in Section 2. In Section 3 we recall adaptive discretization and a posteriori error analysis for both boundary value and eigenvalue problems. Section 4 then discusses coupling of the discretization and the linear algebraic computation in the AFEM context. Some concluding remarks are given in Section 5.

Our presentation is addressed to nonspecialists, and therefore we keep technical details at a minimum. Such details can be found in the references that are cited throughout the text.

## 2 Model problems, the FEM, and a priori analysis

In this section we introduce basic notation, standard model problems, and the general context of the results stated in the following sections. Many readers are certainly familiar with the presented concepts, but we believe it is useful to recall them here for completeness. As mentioned above, we restrict ourselves to linear, elliptic and selfadjoint model problems, and we focus on the Galerkin-FEM rather than on more general (Petrov-Galerkin) methods. Extended treatments of the FEM and its many variants can be found in numerous books devoted to this method and its applications; see, e.g. [15, 34, 49, 50, 61, 69, 105, 120, 124].

## 2.1 Boundary value model problem and the Galerkin method

We start with the standard variational formulation of a linear boundary value problem:

$$\text{Find } u \in V \text{ such that } \mathfrak{a}(u, v) = \ell(v) \text{ for all } v \in V, \quad (1)$$

where  $V$  is a real Hilbert space with scalar product  $(\cdot, \cdot)_V$  and the associated norm  $\|\cdot\|_V$ ,  $\mathfrak{a} : V \times V \rightarrow \mathbb{R}$  is a bilinear form, and  $\ell : V \rightarrow \mathbb{R}$  is a bounded linear functional. Throughout this paper we assume that  $\mathfrak{a}(\cdot, \cdot)$  satisfies the following conditions:

1.  $\mathfrak{a}(\cdot, \cdot)$  is *symmetric*:  $\mathfrak{a}(v, w) = \mathfrak{a}(w, v)$  for all  $v, w \in V$ .
2.  $\mathfrak{a}(\cdot, \cdot)$  is *continuous (or bounded)*:  
There exists a real constant  $\alpha > 0$  such that  $\mathfrak{a}(w, v) \leq \alpha \|w\|_V \|v\|_V$  for all  $w, v \in V$ .
3.  $\mathfrak{a}(\cdot, \cdot)$  is *coercive (or V-elliptic)*:  
There exists a real constant  $\beta > 0$  such that  $\mathfrak{a}(w, w) \geq \beta \|w\|_V^2$  for all  $w \in V$ .

Because of conditions 2. and 3., the classical Lax-Milgram Lemma [85] (see, e.g. [61, Theorem 2.12, p. 52], [69, Theorem 6.5.9, p. 140] or [105, Theorem 5.5.1, p. 133]), implies that the variational problem (1) has a unique solution that depends continuously on the given data. Since the bilinear form  $\mathfrak{a}(\cdot, \cdot)$  is coercive and symmetric, it defines a scalar product on  $V$ . The associated norm

$$\|v\| \equiv \mathfrak{a}(v, v)^{1/2}$$

is called the *energy norm* on  $V$ .

A widely used example where all conditions on  $\mathfrak{a}(\cdot, \cdot)$  are satisfied is the Poisson equation  $-\Delta u = f$  in a polyhedral domain  $\Omega \subset \mathbb{R}^d$  ( $d = 1, 2$ , or  $3$ ) with a given function  $f \in L^2(\Omega)$  and with homogeneous Dirichlet boundary conditions,  $u = 0$  on  $\partial\Omega$ . The variational formulation of this problem is of the form (1) with

$$\begin{aligned} V &\equiv H_0^1(\Omega) \equiv \{v \in L^2(\Omega) \mid \nabla v \in [L^2(\Omega)]^d, v = 0 \text{ on } \partial\Omega \text{ in the sense of traces}\}, \\ \mathfrak{a}(w, v) &\equiv \int_{\Omega} \nabla w \cdot \nabla v \, d\Omega, \\ \ell(v) &\equiv \int_{\Omega} f v \, d\Omega. \end{aligned} \quad (2)$$

Many results stated in this paper were (first) derived in the context of this model problem.

Note that continuous bilinear forms on  $V \times V$  can be identified with continuous linear mappings from  $V$  to its dual space  $V'$ . Denoting by  $\langle \cdot, \cdot \rangle$  the  $V' \times V$  duality pairing, this is done by considering, for a fixed  $u$ , the linear mapping  $T$  from  $V$  to  $V'$  given by

$$\langle Tu, v \rangle = \mathfrak{a}(u, v) = \ell(v) = \langle f, v \rangle. \quad (3)$$

This mapping is coercive and continuous if the bilinear form  $\mathfrak{a}(\cdot, \cdot)$  is. Given the mapping, it can of course be used to define the bilinear forms. Summarizing, using  $T : V \rightarrow V'$ , the variational formulation (1) can be written as an operator equation in the dual space  $V'$ , i.e.

$$Tu = f, \text{ where } f \in V'; \quad (4)$$

for a concise description see [79, Section 2] and for details see, e.g. [34, Section 2.7], [35, p. 81] or [58, Section 5.9.1 and Chapter 6]. The formulation (4) is conveniently used in numerical analysis of PDE boundary value problems.

Using the inequalities of the Lax-Milgram Lemma one can show that the  $V$ -norm of the discretization error is bounded as

$$\|u - u_h\|_V \leq \frac{\alpha}{\beta} \min_{v_h \in V_h} \|u - v_h\|_V. \quad (5)$$

This result is known as Céa's Lemma [46, Proposition 3.1]; see, e.g. [61, p. 61], [69, Theorem 8.2.1, p. 168] or [105, Theorem 5.2.1, p. 137].

For  $V = H^1(\Omega) \equiv \{v \in L^2(\Omega) \mid \nabla v \in [L^2(\Omega)]^d\}$  and the corresponding norm,

$$\|w\|_{H^1(\Omega)} \equiv \left( \int_{\Omega} (w^2 + \nabla w \cdot \nabla w) d\Omega \right)^{1/2} \quad \text{for all } w \in H^1(\Omega),$$

it can be shown that

$$\|w\| \leq \|w\|_{H^1(\Omega)} \leq c \|w\| \quad \text{for all } w \in H_0^1(\Omega), \quad (6)$$

where the energy norms on the left and right correspond to the bilinear form  $\mathfrak{a}(\cdot, \cdot)$  from the Poisson model problem (2), and  $c > 0$  is some generic constant<sup>1</sup> that is independent of  $w$ . In the context of the Poisson model problem the norm equivalence expressed in (6) allows to derive error bounds with respect to the  $H^1(\Omega)$ -norm from those for the energy norm, and vice versa.

Here it is important to point out some differences between analysis of PDEs and numerical solution of PDEs. While in analysis the (topological) equivalence of norms represents a basic tool, in computations one should always specify the possible size of any unspecified constant. As an example, if we solve the discretized problem iteratively, it does make a difference in which norm (or, more generally, in which way) we measure the distance of the computed approximation to the true solution. The algebraic error should, as a rule, be measured in a norm conforming to the underlying PDE or its variational formulation. Hence, in particular, the algebraic residual norm should not be used for stopping the algebraic iterations unless there is a well justified reason for doing so; for further comments on this issue see Section 4 below.

We will now consider the *Galerkin method* for finding an approximation to the solution of a variational problem of the form (1). In this method one chooses a finite dimensional subspace  $V_h \subset V$  and then solves the variational problem on  $V_h$ :

$$\text{Find } u_h \in V_h \text{ such that } \mathfrak{a}(u_h, v_h) = \ell(v_h) \text{ for all } v_h \in V_h. \quad (7)$$

By the assumptions on  $\mathfrak{a}(\cdot, \cdot)$  and  $\ell(\cdot)$ , and since  $V_h$  is a subspace of  $V$ , the Lax-Milgram Lemma implies that (7) has a uniquely determined solution  $u_h$ . For any  $v_h \in V_h$  we have the *Galerkin orthogonality property*

$$\mathfrak{a}(u - u_h, v_h) = \mathfrak{a}(u, v_h) - \mathfrak{a}(u_h, v_h) = \ell(v_h) - \ell(v_h) = 0, \quad (8)$$

<sup>1</sup> Throughout this paper we use, for ease of notation, the letter  $c$  to denote a constant independent of the solution  $u$ . The actual values of  $c$  will be different in different contexts.

which means that the *discretization error*  $u - u_h \in V$  is orthogonal to the subspace  $V_h$  with respect to the scalar product  $\mathbf{a}(\cdot, \cdot)$  on  $V$ . This implies that the method is optimal with respect to the energy norm, i.e. the discretization error satisfies

$$\|u - u_h\| = \min_{v_h \in V_h} \|u - v_h\|. \quad (9)$$

The bounds (5) and (9) are essential ingredients in the *a priori error analysis* of the FEM for boundary value problems; see Section 2.3 below.

Let  $V_h$  be of dimension  $n_h$ , and let  $\phi_1, \phi_2, \dots, \phi_{n_h}$  be a basis of  $V_h$ . Then we can write

$$u_h = \sum_{j=1}^{n_h} \mu_{h,j} \phi_j, \quad (10)$$

where the coefficients in this linear combination are to be determined. This can be done by rewriting the problem (7) in the form

$$\begin{aligned} &\text{Find } \mu_{h,1}, \mu_{h,2}, \dots, \mu_{h,n_h} \in \mathbb{R} \text{ such that} \\ &\sum_{j=1}^{n_h} \mathbf{a}(\phi_j, \phi_i) \mu_{h,j} = \ell(\phi_i) \text{ for all } i = 1, 2, \dots, n_h, \end{aligned}$$

which is equivalent to finding the solution  $\mathbf{u}_h = [\mu_{h,i}] \in \mathbb{R}^{n_h}$  of the linear algebraic system

$$\mathbf{A} \mathbf{u}_h = \mathbf{b}, \quad \mathbf{A} = [a_{ij}] = [\mathbf{a}(\phi_j, \phi_i)] \in \mathbb{R}^{n_h \times n_h}, \quad \mathbf{b} = [b_i] = [\ell(\phi_i)] \in \mathbb{R}^{n_h}. \quad (11)$$

The matrix  $\mathbf{A}$ , which by our assumptions on  $\mathbf{a}(\cdot, \cdot)$  is symmetric and positive definite, is often called the *stiffness matrix*. This term goes back to early applications of the method in structural mechanics.

Suppose that

$$\mathbf{u}_h^{(n)} = [\mu_{h,i}^{(n)}] \in \mathbb{R}^{n_h}$$

is an approximation of the vector  $\mathbf{u}_h$ , with the corresponding approximation of the function  $u_h \in V_h$  given by

$$u_h^{(n)} \equiv \sum_{j=1}^{n_h} \mu_{h,j}^{(n)} \phi_j \in V_h.$$

Then the *algebraic error* is

$$\mathbf{u}_h - \mathbf{u}_h^{(n)} \in \mathbb{R}^{n_h} \quad \text{or} \quad u_h - u_h^{(n)} \in V_h.$$

The *total error* is given by the the sum of the discretization error and the algebraic error, i.e.

$$u - u_h^{(n)} = (u - u_h) + (u_h - u_h^{(n)}). \quad (12)$$

Since  $u_h - u_h^{(n)} \in V_h$ , the Galerkin orthogonality property (8) implies that

$$\|u - u_h^{(n)}\|^2 = \|u - u_h\|^2 + \|u_h - u_h^{(n)}\|^2. \quad (13)$$

This equality for the energy norms of the respective quantities indicates that in practical applications the discretization error and the algebraic error should be in a reasonable balance,

so that neither one of them dominates the total error. This observation has important consequences for coupling of the linear algebraic computations with the FEM discretization in particular in the AFEM context. We will explore these consequences in Section 4 below.

It is worth to point out that in (13) the relation between the total error, the discretization error and the algebraic error is described in terms of their global norms. In the context of adaptive numerical solution of PDEs this is not sufficient. For an instructive discussion of this point we refer to the book [15], where Babuška and Strouboulis state on p. 417:

In engineering practice it is not sufficient to estimate only the energy norm of the error because *a small value of the global energy norm of the error does not necessarily imply that the error in the outputs of interest is also small* (e.g. a 5% relative error in the global energy norm does not imply 5% relative error in the maximum stress in a region of interest). ... An essential requirement is that the quantity of interest has to be well defined; for example, it is meaningless to ask for an estimate of the maximum error in the derivative, flux, or stress for a problem set in a polygonal non-convex domain, because the exact value does not exist (the derivative, flux, or stress in the neighborhood of a corner point is usually unbounded).

Moreover, there is no guarantee that the spatial distributions of the (properly measured) discretization error and algebraic error are similar; see [86, Chapter 5] and [101] for illustrations of this fact. When evaluating the local error indicators in practice one should therefore consider *local* distributions of the appropriately measured *individual* errors  $u - u_h^{(n)}$  and  $u_h - u_h^{(n)}$ .

## 2.2 Eigenvalue model problem and the Galerkin method

The standard variational formulation of a linear PDE eigenvalue (and eigenfunction) problem considered in this paper can be written as follows:

$$\text{Find } u \in V \setminus \{0\} \text{ and } \lambda \in \mathbb{R} \text{ such that } \mathfrak{a}(u, v) = \lambda (u, v)_W \text{ for all } v \in V. \quad (14)$$

Here  $V, W$  are two real Hilbert spaces such that the embedding  $V \subset W$  is compact and  $V$  is dense in  $W$ ,  $(\cdot, \cdot)_W$  is the scalar product on  $W$ , and  $\mathfrak{a} : V \times V \rightarrow \mathbb{R}$  is a (symmetric, continuous and coercive) bilinear form.

A standard example is given by the Poisson eigenvalue (and eigenfunction) model problem formulated in a polyhedral domain  $\Omega \subset \mathbb{R}^d$  ( $d = 1, 2$ , or  $3$ ) with homogeneous Dirichlet boundary conditions. The task is to find a nonzero function  $u : \overline{\Omega} \rightarrow \mathbb{R}$  and a scalar  $\lambda \in \mathbb{R}$ , such that  $-\Delta u = \lambda u$  in  $\Omega$ , where  $u = 0$  on  $\partial\Omega$ . The variational formulation of this problem is given by (14) with

$$\begin{aligned} V &\equiv H_0^1(\Omega) \subset W \equiv L^2(\Omega), \\ \mathfrak{a}(w, v) &\equiv \int_{\Omega} \nabla w \cdot \nabla v \, d\Omega, \\ (w, v)_W &\equiv \int_{\Omega} w v \, d\Omega. \end{aligned} \quad (15)$$

Consider, for any given  $f \in V$ , the following (variational) boundary value problem:

$$\text{Find } z \in V \text{ such that } \mathfrak{a}(z, v) = (f, v)_W \text{ for all } v \in V.$$

By our assumptions on  $\mathfrak{a}(\cdot, \cdot)$  this problem has a unique solution  $z \in V$ . Hence we can introduce the (linear and compact) *solution operator*  $S : V \rightarrow V$  such that

$$\mathfrak{a}(Sf, v) = (f, v)_W \text{ for all } v \in V. \quad (16)$$

Since  $\mathfrak{a}(\cdot, \cdot)$  is symmetric and coercive, which holds in particular for  $\mathfrak{a}(\cdot, \cdot)$  in (15), the operator  $S$  has countably many eigenvalues that are real and positive. Their reciprocals, denoted by

$$0 < \lambda_1 \leq \lambda_2 \leq \dots \leq \lambda_m \leq \dots,$$

give the eigenvalues of the problem (14); see, e.g. [13, p. 650], [58, p. 355] or [69, Theorem 11.1.2, p. 253–254]. The corresponding (normalized) eigenfunctions  $u_j$  form an orthonormal basis for the space  $W$ ; see, e.g. [58, p. 355]. Using the operator  $S$  with  $f = u$  and (14) we get

$$\mathfrak{a}(Su, v) = (u, v)_W = \frac{1}{\lambda} \mathfrak{a}(u, v) = \mathfrak{a}\left(\frac{1}{\lambda}u, v\right) \text{ for all } v \in V.$$

Hence  $\{\lambda, u\}$  is a solution of the eigenvalue problem (14) if and only if  $\{\frac{1}{\lambda}, u\}$  is an eigenpair of the operator  $S$ . For further details see, e.g. [47, Chapter 4, pp. 203–204], [58, p. 355–356] or [30, 81, 116].

Analogously to the Galerkin method for boundary value problems, the Galerkin method for the eigenvalue problem (15)–(14) consists in solving the variational problem on a finite dimensional subspace  $V_h \subset V$ :

$$\begin{aligned} &\text{Find } u_h \in V_h \setminus \{0\} \text{ and } \lambda_h \in \mathbb{R} \text{ such that} \\ &\mathfrak{a}(u_h, v_h) = \lambda_h (u_h, v_h)_W \text{ for all } v_h \in V_h. \end{aligned} \quad (17)$$

As in the previous section, let  $n_h$  be the dimension of  $V_h$ , and let  $\phi_1, \phi_2, \dots, \phi_{n_h}$  be a basis of  $V_h$ . Writing the function  $u_h$  as a linear combination of the basis functions (as in (10)), the problem (17) can be transformed into the equivalent *generalized algebraic eigenvalue problem*

$$\mathbf{A} \mathbf{u}_h = \lambda_h \mathbf{M} \mathbf{u}_h, \quad \text{where}$$

$$\mathbf{A} = [a_{ij}] = [\mathfrak{a}(\phi_j, \phi_i)] \in \mathbb{R}^{n_h \times n_h}, \quad \mathbf{M} = [m_{ij}] = [(\phi_j, \phi_i)_W] \in \mathbb{R}^{n_h \times n_h},$$

for the eigenvalue  $\lambda_h \in \mathbb{R}$  and a corresponding eigenvector  $\mathbf{u}_h \in \mathbb{R}^{n_h}$ . The matrix  $\mathbf{A}$  is (as above) called the *stiffness matrix*, and  $\mathbf{M}$  is the *mass matrix*.

Both  $\mathbf{A}$  and  $\mathbf{M}$  are symmetric positive definite (since both  $\mathfrak{a}(\cdot, \cdot)$  and  $(\cdot, \cdot)_W$  are scalar products), and hence the problem (17) has a finite sequence of eigenvalues

$$0 < \lambda_{h,1} \leq \lambda_{h,2} \leq \dots \leq \lambda_{h,n_h}$$

with the corresponding eigenvectors  $\mathbf{u}_{h,1}, \mathbf{u}_{h,2}, \dots, \mathbf{u}_{h,n_h} \in \mathbb{R}^{n_h}$  that can be chosen  $\mathbf{M}$ -orthonormal, i.e.  $\mathbf{u}_{h,i}^T \mathbf{M} \mathbf{u}_{h,j} = \delta_{ij}$ . They determine, analogously to (10), the respective eigenfunction approximations  $u_{h,1}, u_{h,2}, \dots, u_{h,n_h} \in V_h$ . The eigenvalue  $\lambda_{h,j}$  and the corresponding function  $u_{h,j}$  are called the *Galerkin approximation* of the  $j$ -th eigenvalue  $\lambda_j$  and the corresponding eigenfunction  $u_j$  of the problem (14). From the Courant-Fischer minimax theorem it directly follows that

$$\lambda_j \leq \lambda_{h,j}, \quad j = 1, 2, \dots, n_h;$$

see, e.g. [13, equation (8.42), p. 699] or [124, equation (23), p. 223].

If we solve the generalized eigenvalue problem inexactly, and hence obtain an eigenvector approximation  $\mathbf{u}_{h,j}^{(n)}$  and a corresponding eigenvalue approximation  $\lambda_{h,j}^{(n)}$ , we get the *algebraic errors*

$$\mathbf{u}_{h,j} - \mathbf{u}_{h,j}^{(n)} \in \mathbb{R}^{n_h} \quad \text{or} \quad u_{h,j} - u_{h,j}^{(n)} \in V_h, \quad \text{and} \quad \lambda_{h,j} - \lambda_{h,j}^{(n)}.$$

The *total errors* are then given by

$$u_j - u_{h,j}^{(n)} = (u_j - u_{h,j}) + (u_{h,j} - u_{h,j}^{(n)}) \quad \text{and} \quad (18)$$

$$\lambda_j - \lambda_{h,j}^{(n)} = (\lambda_j - \lambda_{h,j}) + (\lambda_{h,j} - \lambda_{h,j}^{(n)}). \quad (19)$$

In both cases the total error is the sum of the discretization error and the algebraic error.

All this looks very similar to the formulations for the boundary value problems in the previous section. However, results obtained for boundary value problems can typically not be directly transferred because eigenvalue problems are by their nature *nonlinear*. In particular, there exists no simple analogy to the Galerkin orthogonality property (8) for the boundary value problems: When  $\{\lambda, u\}$  and  $\{\lambda_h, u_h\}$  are eigenpairs of (14) and (17), respectively, we get

$$\mathbf{a}(u - u_h, v_h) = (\lambda u - \lambda_h u_h, v_h)_W. \quad (20)$$

This is usually nonzero for any nonzero  $v_h \in V_h$ .

### 2.3 The FEM and a priori error estimation

The FEM (more precisely, the Galerkin-FEM) generates the subspace  $V_h$  in order to obtain a *sparse* matrix  $\mathbf{A}$ , respectively *sparse* matrices  $\mathbf{A}$  and  $\mathbf{M}$ . The method is based on a decomposition of  $\overline{\Omega}$  into a finite number of subdomains  $\tau_j$ , called the *elements*. In case  $\Omega$  is a polyhedral domain one typically considers simplicial elements. Popular choices are triangles when  $\Omega \subset \mathbb{R}^2$ , and tetrahedra when  $\Omega \subset \mathbb{R}^3$ . We denote by  $\mathcal{T}_h$  the set of all the elements in the decomposition  $\overline{\Omega} = \cup_j \tau_j$ . This decomposition is called the *mesh*, with the *mesh size*  $h$  given by the maximal diameter of any element. A standard assumption is that each intersection of two distinct elements is either empty, or a common vertex, or a common edge in  $\mathbb{R}^2$  (a common face or a common edge in  $\mathbb{R}^3$ ) of the two elements.

In the standard FEM, the finite element basis functions  $\phi_1, \phi_2, \dots, \phi_{n_h}$  are globally (i.e. throughout  $\Omega$ ) continuous functions that are piecewise (i.e. on individual elements) polynomials, and that are nonzero only on a few of the elements. Considering higher-degree polynomials but preserving the geometry of the mesh is called a *p-refinement*. Below we will mostly consider *h-refinements*, also called *mesh refinements*, where the decomposition of  $\overline{\Omega}$  is refined by subdividing elements.

When the supports of  $\phi_i$  and  $\phi_j$  do not overlap, the corresponding entries  $a_{ij} = \mathbf{a}(\phi_j, \phi_i)$  of  $\mathbf{A}$  and  $m_{ij} = (\phi_j, \phi_i)_W$  of  $\mathbf{M}$  will be zero. Hence the local nature of the FEM basis functions guarantees sparsity of the stiffness and mass matrices. At the same time it means that the solutions  $u_h$  of the variational problem (7) or  $u_{h,j}$  of the problem (17) are linear combinations of functions with significantly local supports. The global approximation properties of  $u_h$  or  $u_{h,j}$  have to be obtained by solving the linear algebraic system or the algebraic eigenvalue problem.

Standard *a priori convergence theory* for the FEM is concerned with bounding the discretization error of the boundary value or the eigenvalue problem *globally* in some norm. We point out that the choice of the polynomial degree used for the basis of the FEM approximation is linked with the *regularity of the solution* of the boundary value problem or of the eigenfunctions we want to approximate; see, e.g. [68] for an extensive analysis of the regularity of the solutions when  $\Omega$  is not convex, and [11, 124] for the convergence analysis for Sobolev spaces  $H^s(\Omega)$  for real  $s$  (so-called fractional order Sobolev spaces [1]). Under some *regularity assumptions on the mesh*, the usual goal of an *a priori* analysis is to find bounds on the discretization error that depend on the mesh size  $h$ . For example, a standard regularity assumption used in the context of triangular meshes is a minimum angle condition to guarantee that the interior angles of the elements do not become too acute; see, e.g. [55, Definition 1.15, p. 44] or [124, Chapter 3, Section 3.1 and 3.2].

A classical result for boundary value problems of the form (1) on a polygonal domain  $\Omega \subset \mathbb{R}^2$  can be formulated as follows: If  $\mathfrak{a}(\cdot, \cdot)$  and  $\ell(\cdot)$  satisfy the Lax-Milgram conditions, the solution satisfies  $u \in H^s(\Omega)$  for some integer  $s > 1$ , the FEM basis functions are (locally) polynomials of degree  $k$ , where  $1 \leq k < s$ , and the triangular mesh is regular, then

$$\|u - u_h\|_{H^1(\Omega)} \leq c \|u\|_{H^{r+1}(\Omega)} h^r, \quad \text{where } r \equiv \min(k, s - 1). \quad (21)$$

Here  $c > 0$  is a constant depending on the ratio  $\alpha/\beta$  (from the Lax-Milgram conditions) and on the minimum angle in the mesh, but  $c$  does not depend on the mesh size  $h$  and the solution  $u$ . This result can be generalized to real values of  $s$  [11]; see also [69, Theorem 8.4.8, p. 189] for the case  $1 < s \leq 2$ , [105, Theorem 6.2.1, p. 171] for the case  $s \geq 2$ , and the classical book [50] for a general treatment. A less technical presentation valid for integer  $s > 1$  is given in [61, Section 5.3]. The exponent  $r$  on the right hand side of (21) is called the method's *rate of convergence*. The inequality indicates that when the solution is sufficiently smooth, higher degree finite elements (i.e. *p*-refinement) yield a larger rate of convergence. Results of the form (21) are derived by bounding the minimization problem on right hand side of (5) or (9).

In eigenvalue problems the analysis is complicated due to the lack of a Galerkin-type orthogonality property; see Section 2.2 above. Nevertheless, one can derive *a priori* bounds on the discretization error that depend on the regularity of the eigenfunction and hence, in particular, on the geometry of the domain  $\Omega$ ; see, e.g. [124, Chapter 8] or [68] for details on the regularity of eigenfunctions.

One of the first *a priori* error results for eigenvalues and eigenfunctions of elliptic operators was obtained by Strang and Fix in [124, Chapter 6], where the eigenfunction approximations are determined by the Rayleigh-Ritz method, i.e. as the stationary (fixed) points of the Rayleigh-quotient  $\mathfrak{a}(\cdot, \cdot)/(\cdot, \cdot)_W$ . Improvements for selfadjoint operators were made in [47, 80, 111], and for compact operators in [12, 13].

To state a well known *a priori* error bound for the problem (14) with  $\mathfrak{a}(\cdot, \cdot)$  symmetric and satisfying the Lax-Milgram conditions, suppose that  $\{\lambda, u\}$  is an eigenpair, where  $\lambda$  is a simple eigenvalue and the eigenfunction satisfies  $u \in H^s(\Omega)$  for some (real)  $s \in (1, 2]$ . When the triangular mesh is regular and linear finite elements are used, there exists an eigenpair  $\{\lambda_h, u_h\}$  of the discretized problem (17) such that

$$\|u - u_h\|_{H^1(\Omega)} \leq c h^{s-1} \quad \text{and} \quad |\lambda - \lambda_h| \leq c h^{2(s-1)}, \quad (22)$$

where the constant  $c > 0$  depends on the eigenvalue  $\lambda$ , the eigenfunction  $u$ , and on the mesh; see, e.g. [69, Corollary 11.2.21, p. 264]. A key observation to be made in (22), which is also made in the standard matrix perturbation theory, is that the eigenvalue approximation is usually much more accurate than the corresponding eigenfunction approximation. A generalization of this result to the case of multiple eigenvalues is given by Babuška and Osborn in [13]; see also the recent survey paper [30].

### 3 Adaptivity and a posteriori estimators

*A priori* bounds of the form (21) or (22) indicate that the discretization error decreases (at least asymptotically) with a decreasing mesh size  $h$ . Since  $h$  is the maximum diameter of any element, we get  $h \rightarrow 0$  only if the mesh is refined *everywhere*. Such refinement, however, is costly and it is usually prohibitive in challenging practical applications. The key idea of adaptive mesh refinement is to refine the mesh only where it is necessary. This requires information on the local distribution of the error within the domain, which is provided by a locally efficient and computable *a posteriori error estimator*. In the following we will summarize main ideas of a posteriori error estimation in the FEM context. For further details we refer in particular to the books [3, 15, 17, 128], or the surveys given in [56, 66, 96, 99, 117].

Using an appropriate norm induced by a scalar product on  $L^2(\Omega)$  or  $H^1(\Omega)$ , an *a posteriori* error estimator for a stationary boundary value problem like (1)–(3) is typically written as

$$\|u - u_h\| \approx \eta, \quad \eta \equiv \left( \sum_{\tau \in \mathcal{T}_h} \eta_\tau^2 \right)^{1/2} \quad (23)$$

(similarly for the eigenvalue problem), where  $\eta_\tau$  is an indicator for the local error on the element  $\tau$ . This indicator depends on  $u_h$  and some known information about the problem, for example the domain  $\Omega$  and its boundary. Other forms of *a posteriori* error estimators can be found, e.g., in [3, Section 2.5].

A *a posteriori* error estimators should be computable from  $u_h$  at a low cost, and they should ideally satisfy the following additional properties:

1. *Reliability (guaranteed upper bound)*: The right hand side in the approximation (23) represents an upper bound on the left hand side,

$$\|u - u_h\| \leq \left( \sum_{\tau \in \mathcal{T}_h} \eta_\tau^2 \right)^{1/2}.$$

This definition of reliability corresponds to the ideal situation where the estimator on the right hand side is not multiplied by a constant  $c > 0$ . Some important estimators satisfy a weaker form of reliability, where a constant  $c$  is present; see, e.g. (25)–(26) below.

2. *Local efficiency*: For each element  $\tau \in \mathcal{T}_h$  the corresponding  $\eta_\tau$  represents a lower bound on the error in the vicinity  $\hat{\tau}$  of  $\tau$  (typically  $\hat{\tau}$  is the union of  $\tau$  and its neighbors) up to a mesh size independent constant  $c > 0$ ,

$$\eta_\tau \leq c \|u - u_h\|_{\hat{\tau}} + h.o.t. \quad \text{for all } \tau \in \mathcal{T}_h.$$

The constant  $c$  should not be close to zero and it should not be substantially (orders of magnitude) larger than one; *h.o.t.* represents a higher order term related to data oscillations.

3. *Asymptotic exactness*: The ratio of the error and its estimator in (23) approaches one when the estimators are used to locally refine the mesh within the AFEM loop (cf. the Introduction).

It is highly desirable that the a posteriori estimators are also *robust*, i.e. the above mentioned properties should hold for a wide range of parameters defining the practical problems. Not every existing a posteriori estimator satisfies all these desirable properties. In the following we will give examples of some techniques and mention which properties have been shown for them.

For a typical example we consider the variational boundary value model problem (1)–(2) in a bounded polygonal domain  $\Omega \subset \mathbb{R}^2$  and its Galerkin discretization as in (7). Let  $\mathcal{T}_h$  be a regular triangulation of  $\Omega$ . Considering the discretization error  $u - u_h$  and any given  $v \in V$  we can write

$$\mathfrak{a}(u - u_h, v) = \ell(v) - \mathfrak{a}(u_h, v) = \sum_{\tau \in \mathcal{T}_h} \left( \int_{\tau} f v d\tau - \int_{\tau} \nabla v \cdot \nabla u_h \right). \quad (24)$$

Let  $\mathcal{E}_h$  be the set of edges in the triangulation  $\mathcal{T}_h$  excluding the boundary of  $\Omega$ . For a scalar function  $w$  that is defined in an open neighborhood of  $\varepsilon \in \mathcal{E}_h$  one defines the *jump across*  $\varepsilon$  by

$$[w](x) \equiv \lim_{t \rightarrow 0} (w(x - t\mathbf{n}_{\varepsilon}) - w(x + t\mathbf{n}_{\varepsilon})), \quad x \in \varepsilon,$$

where  $\mathbf{n}_{\varepsilon}$  denotes the outward normal of  $\varepsilon$  (this is defined analogously in  $\mathbb{R}^3$  for element faces). Let  $h_{\tau}$  and  $h_{\varepsilon}$  denote the mesh sizes of the element  $\tau$  and the edge  $\varepsilon$ , respectively. Substituting  $v = u - u_h \in V$  in (24), and using the Galerkin orthogonality property, integration by parts and some subtle technical ingredients, one obtains the *a posteriori bound*

$$\|u - u_h\|^2 \leq c \eta_{res, \mathcal{T}_h}^2, \quad \text{where} \quad (25)$$

$$\eta_{res, \mathcal{T}_h} \equiv \left( \sum_{\tau \in \mathcal{T}_h} h_{\tau}^2 \|\Delta u_h + f\|_{L^2(\tau)}^2 + \sum_{\varepsilon \in \mathcal{E}_h} h_{\varepsilon} \|\nabla u_h \cdot \mathbf{n}_{\varepsilon}\|_{L^2(\varepsilon)}^2 \right)^{1/2}; \quad (26)$$

see the original work of Babuška and Rheinboldt in [14] or, e.g. the books [34, Section 9.2], [61, Section 15.2], or [128, Section 1.2].

In (25)–(26) the energy norm of the discretization error is bounded by the sums of local contributions of the *residual*  $\Delta u_h + f$  on the individual elements and of the jumps of the gradient of  $u_h$  at the element edges. The expression (26) is called *residual a posteriori error estimator*. The value of the constant  $c$  is in principle computable (even if quite costly). It depends on the minimal angle allowed in the mesh elements, on the Poincaré-Friedrichs inequality constant (which is a function of the volume of  $\Omega$  and the area of the portion of  $\partial\Omega$  where the Dirichlet condition are imposed; see [128, p. 11]), and, in an analogous estimator for a more general  $\mathfrak{a}(\cdot, \cdot)$ , on the constants  $\alpha$  and  $\beta$  from the Lax-Milgram conditions. However, the possibly large value of  $c$  can produce a significant overestimate of the error; see,

e.g. [39, 48]. The residual a posteriori error estimator satisfies the property 1. (reliability) in a weaker form, namely with the estimator multiplied by a suitable constant  $c > 0$  (see (25)–(26) and the evaluation of  $c$  in, e.g. [39, 40, 126]), and it satisfies the property 2. (local efficiency); for the proofs see, e.g. [3, 128]. The third property (asymptotic exactness) usually does not hold in practical computations.

Analogous residual estimators can be derived for the variational eigenvalue model problem (14)–(15) and its Galerkin discretization (17). Here the interior element residual is given by the function  $\Delta u_h + \lambda_h u_h$ , and one obtains the bound

$$\|u - u_h\|^2 \leq c \eta_{res, \mathcal{T}_h} \|u - u_h\| + \frac{\lambda + \lambda_h}{2} \|u - u_h\|_{L^2(\Omega)}^2, \quad (27)$$

$$\eta_{res, \mathcal{T}_h} \equiv \left( \sum_{\tau \in \mathcal{T}_h} h_\tau^2 \|\Delta u_h + \lambda_h u_h\|_{L^2(\tau)}^2 + \sum_{\varepsilon \in \mathcal{E}_h} h_\varepsilon \|\nabla u_h \cdot \mathbf{n}_\varepsilon\|_{L^2(\varepsilon)}^2 \right)^{1/2}, \quad (28)$$

where for  $c$  the above considerations are valid; see [31, Section 6.3], [54, Theorem 3.1], [132, Section 4], or the earlier work of Larson [84]. It was shown that the  $L^2$ -norm of the error is of higher order than the energy norm of the error (see [54]), so that (27)–(28) indeed represents an a posteriori estimate for the energy norm of the error. As for the properties 1.–3., the situation is analogous to (25)–(26) for the boundary value problem; for a proof see, e.g. [54].

The residual a posteriori estimators, though well-understood and well-established in practice, may significantly overestimate the actual error. The reason is that the constant  $c$  present in the bounds may be very large. Therefore, several other techniques were introduced over the last years, and they can be classified as follows (see, e.g. [3, 49, 128]):

*Local problem-based estimators (implicit estimators):* Instead of considering the original discrete problem, local analogues of the residual equations are solved and suitable norms of the local solutions are used for the error estimation. The local problems usually involve only small subdomains of  $\Omega$  and more accurate finite element approximations. In terms of cost, the solution of all local problems should be much less demanding than assembling the stiffness matrix of the original discrete problem. More details for boundary value problems are given in [3, Chapter 3], [49, Section 6.3.2], [61, Section 15.3], [128, Section 1.3] and [2, 33, 44]. A proof of the property 2. for this type of estimator can be found, e.g., in [3]. The properties 1. and 3. are, in general, not formally proved, but they are often satisfied, in a bit relaxed form, in practical computations. We are not aware of any local problem-based error estimators designed specifically for eigenvalue problems.

*Averaging estimators (recovery-based estimators):* These error estimators use a local extrapolation or averaging technique. The error of the approximation can be controlled by a difference of a low-order approximation (e.g., a piecewise constant function) and a finite element solution obtained in the space of higher-order elements (e.g., globally continuous piecewise linear functions), which additionally satisfy more restrictive continuity conditions than the approximation itself; see, e.g. [3, Chapter 4], [49, Section 6.3.3] or [128, Section 1.5]. Carstensen gives in [38] a nice overview of averaging techniques in a posteriori finite element error analysis in general. Particular error estimators are discussed in [41, 89, 138]. The property 1. can, in general, not be proved for averaging estimators. The proof of property 3. can be found, e.g., in [3, 128], and the property 2. is often satisfied in practice.

*Hierarchical estimators (multilevel estimators):* The main idea of a hierarchical error estimator is to evaluate the residual for the finite element solution  $u_H \in V_H$  with respect to another finite element space  $V_h$  that satisfies  $V_H \subset V_h \subset V$ . Then the error  $\|u - u_H\|$  can be bounded by  $\eta \equiv \|u_h - u_H\|$ , where  $u_h \in V_h$ ; see [19, 52, 59], [49, Chapter 6], or [128, Section 1.4] for details. Usually  $V_h$  corresponds to a refinement  $\mathcal{T}_h$  of  $\mathcal{T}_H$  or consists of higher-order finite elements. This approach takes advantage of the so-called *saturation assumption*; see, e.g. [20]. The error of a fine discrete solution  $u_h$  is supposed to be smaller than the error of the coarse solution  $u_H$  in the sense of an error reduction property, i.e.

$$\|u_h - u\| \leq \gamma \|u_H - u\|, \quad \text{where } \gamma \in (0, 1).$$

Hierarchical error estimators for eigenvalue problems are discussed in [90, 98].

*Estimators based on equilibrated flux reconstruction:* A recent general framework for a posteriori error estimators founded on potential and equilibrated flux reconstruction, which can be traced back to the ideas of Prager and Synge [104] and to the hypercircle method [125], is described in [76, 129, 130]. As recalled in [70], the flux reconstruction idea has been used for construction of a posteriori error estimators by many authors, possibly starting with [83]. The resulting estimators consist of the residual part, the flux part and the so-called nonconformity part, and they can be applied to various discretization methods and inexact computations; see [70, 131]. The following section will present more details. The estimators are proved to satisfy properties 1. and 2., while property 3. typically holds, in a bit relaxed form, in practice.

As an example from the classical approaches based on the flux reconstruction we point out the *equilibrated residual method*, which is comprehensively described (with many references to the original papers) in [3, Chapter 6]. Here the fluxes are reconstructed using the discretized solution  $u_h$ , i.e. it is assumed that the algebraic problems are solved exactly.

Finally, we wish to mention *goal-oriented estimators*, which are more general than the previous approaches estimating (23). The objective in goal-oriented error estimation is to determine the accuracy of the finite element solution  $u_h$  with respect to some physically relevant scalar quantity of the solution  $u$ , the so-called “quantity of interest”  $J(\cdot)$ , e.g., velocity or flow rates. The error in the quantity of interest is then related to the residual, i.e.

$$|J(u) - J(u_h)| \approx \sum_{\tau \in \mathcal{T}_h} \rho_\tau(u_h) \omega_\tau,$$

where  $\rho_\tau(u_h)$  denotes the so-called “cell residuals” of the approximate solution, and  $\omega_\tau$  a corresponding “cell weights”. The latter are obtained from the solution of the so-called *dual problem*. The solution of this problem is typically not available, and in practice it is replaced by some local postprocessing of the computed discrete approximation. One of the well-known techniques of goal-oriented error estimation is the *Dual Weighted Residual (DWR)* method introduced by Rannacher in [106]. More details on this method and many further references are given in the following section. Approaches based on goal oriented estimators such as DWR do not typically aim at proving the properties 1.–3. from above. They, however, target a much more difficult result and allow complicated settings without strong assumptions on the problem to be solved, and they are very successful in most of their practical applications.

## 4 Coupling discretization with algebraic computation

As described in the Introduction, the AFEM is an iterative procedure consisting of the four steps SOLVE, ESTIMATE, MARK, and REFINE. It starts with an initial (usually coarse) mesh  $\mathcal{T}_{h_0}$  and a corresponding finite element space  $V_{h_0}$ . The finite element approximation of the continuous solution obtained in the first SOLVE step is used in the following ESTIMATE step for the local a posteriori estimation of the error. This estimation yields a set of elements on which the local error is indicated too large, so that a refinement is necessary. The actual refinement procedure happens in the steps MARK and REFINE (see [17, 33, 53] for details), and it leads to a mesh  $\mathcal{T}_{h_1}$  and a corresponding finite element space  $V_{h_1}$ . The AFEM loop is continued in this way until the a posteriori estimator indicates that no further refinement is necessary. It should also be pointed out that although the last step is called REFINE, it can also include a possible coarsening of the mesh in the areas where the error appears to be small.

This description, the bounds in the previous section, and the majority of the AFEM publications are based on *exact* solutions of the linear algebraic problems. This is an acceptable assumption when the cost for solving these problems is small and the problems are well conditioned independently of the mesh refinement (results in this direction can be found, e.g., in [18] and [34, Section 9.5]). In real-world applications, however, adaptive finite element methods can lead to very large and possibly ill-conditioned linear algebraic problems. Consequently, in practical applications an exact (i.e. to machine precision) solve of the related linear algebraic problems is not possible. Here it is important to point out that the accuracy can not be measured by the algebraic residual; cf. the quote from the paper by Becker, Johnson and Rannacher [22] in the Introduction. Some works suggest the algebraic residual as a measure of convergence in the numerical PDE context even for the Conjugate Gradient (CG) method [72]; see, e.g. [103]. It should be understood that unless the problem is easily preconditioned, this approach hardly can work in practice. The arguments can be found already in [72]; for a recent discussion we refer to, e.g., [5, Section 4]. For numerically challenging problems even residuals proportional to machine precision (such as those obtained by direct solvers) do not necessarily guarantee any reasonable accuracy of the computed approximate solution. Moreover, solving the linear algebraic problems to a (much) higher accuracy than the order of the discretization error usually does not improve the overall computed approximate solution and it just inadequately increases the computational cost; see the quote from [22] or [61, Section 13.4.1]. We have also mentioned this fact in our discussion of equations (12)–(13) above.

In practical applications of the AFEM the algebraic error should be considered a part of the estimation of the total error, i.e. one should use some appropriate norm and aim at estimates of the form

$$\|u - u_h^{(n)}\| \approx \eta_n, \quad (29)$$

where  $\eta_n$  is a function of the approximate solution  $u_h^{(n)}$  (or  $\lambda_h^{(n)}$  and  $u_h^{(n)}$ ) of the linear algebraic problem. Moreover, the fact that the algebraic problems are not solved exactly (and the Galerkin orthogonality does not hold when  $u_h$  is replaced by  $u_h^{(n)}$ ) should be in an adequate way taken into account in the *derivation* of (29). The last point is of principal importance. Formulas derived under restrictive assumptions should, in general, only be used when the assumptions are satisfied. Here the situation is somewhat analogous to the algebraic error estimation in the CG method [72], where for a long time formulas were practically used without being justified by a proper rounding error analysis.

An instructive work on adaptive error control in the FEM combined with the multigrid method for solving the discretized problems was published in 1995 by Becker, Johnson, and Rannacher [22], which we already quoted several times above. The authors consider the Poisson problem on a polygonal domain  $\Omega$  and prove a posteriori error estimates in the  $H^1(\Omega)$ - and  $L^2(\Omega)$ -norms that incorporate algebraic errors and design of the adaptive algorithm, and they suggest stopping criteria for the multigrid computations. Although the paper does not explicitly consider quadrature and rounding errors, its approach can be generalized to cover those as well. The only assumption, standard in multigrid computations, which might require further substantial analysis in extension to difficult problems, is that the algebraic problem on the coarsest grid is solved exactly. The authors also point out that the adaptive error control for the multigrid computations is different from the one for CG computations. An extension of the approach from [22] to the Stokes problem was given by Becker in [21]; see also [27].

Guaranteed upper bounds for the total error based on the so-called Repin majorant and not assuming Galerkin orthogonality are thoroughly described by Repin in [112]; see also the nice survey [127]. This approach naturally includes all sources of error (including the discretization and the algebraic error); for another example with this property (though somewhat hidden in the text) we refer to the recent work of Ainsworth and Vejchodský [4]. On the other hand, the general character of the results not taking into account the specifics of the error origin does not allow to distinguish, analyze, and compare parts of the error corresponding to different sources. In particular, these approaches do not consider constructing stopping criteria for algebraic iterative solvers. Results considering balancing the discretization and the algebraic error will be recalled below.

#### 4.1 Results for boundary value problems

For a general variational boundary value problem of the form (1) based on a symmetric and coercive bilinear form  $\mathfrak{a}(\cdot, \cdot)$ , the squared energy norm of the total error is the sum of the squared energy norm of the discretization error and the squared energy norm of the algebraic error; see (13). The second term in (13) is equal to the squared  $\mathbf{A}$ -norm of the error of the linear algebraic system (11), i.e.

$$\|u_h - u_h^{(n)}\|^2 = \|\mathbf{u}_h - \mathbf{u}_h^{(n)}\|_{\mathbf{A}}^2 \equiv (\mathbf{u}_h - \mathbf{u}_h^{(n)})^T \mathbf{A} (\mathbf{u}_h - \mathbf{u}_h^{(n)}). \quad (30)$$

It is well known that  $\mathbf{A}$ -norm of the error is minimized over a Krylov subspace when the CG method is applied to (11); see [72]. This fact makes CG a natural choice for solving (symmetric positive definite) linear algebraic systems in the finite element context; see [55, Chapters 1 and 2] and [86, Chapter 5]. However, due to the presence of the exact Galerkin solution  $u_h$  in the first term on the right hand side of (13), this splitting can not be directly used for practical error evaluation. It also does not allow a *local* comparison of the different parts of the total error (that would require a knowledge of the spatial distribution of the discretization and algebraic parts of the error). This goal can be achieved, to a certain extent, by the following approaches.

*The DWR method for boundary value problems:* This approach, developed by Rannacher, Becker and their collaborators, does not require the bilinear form  $\mathfrak{a}(\cdot, \cdot)$  being symmetric and coercive, and it has been successfully applied to many problems. Based on theoretically supported heuristics, it allows to compare the estimators for the discretization error and the

algebraic error, and to construct adequate stopping criteria for algebraic iterative solvers. In order to outline the main ideas we consider the variational boundary value problem (1). Let the error be controlled by some linear (goal) functional  $J(\cdot)$  defined on  $V$  representing the quantity of interest. The DWR method considers the associated *dual problem*:

$$\text{Find } z \in V \text{ such that } \mathfrak{a}(v, z) = J(v) \text{ for all } v \in V.$$

Since  $J(\cdot)$  is linear,

$$J(u - u_h^{(n)}) = J(u - u_h) + J(u_h - u_h^{(n)}). \quad (31)$$

For any  $v_h \in V_h \subset V$  we can write, using the Galerkin orthogonality property,

$$\begin{aligned} J(u - u_h) &= \mathfrak{a}(u - u_h, z) = \mathfrak{a}(u - u_h, z - v_h) = \ell(z - v_h) - \mathfrak{a}(u_h, z - v_h) \\ &\equiv \rho(u_h)(z - v_h). \end{aligned} \quad (32)$$

The function

$$\rho(u_h)(\cdot) \equiv \ell(\cdot) - \mathfrak{a}(u_h, \cdot)$$

is called the *residual functional* corresponding to the problem (1). Similarly,

$$\begin{aligned} J(u - u_h^{(n)}) &= \mathfrak{a}(u - u_h^{(n)}, z) = \mathfrak{a}(u - u_h^{(n)}, z - v_h) + \mathfrak{a}(u - u_h^{(n)}, v_h) \\ &= \ell(z - v_h) - \mathfrak{a}(u_h^{(n)}, z - v_h) + \ell(v_h) - \mathfrak{a}(u_h^{(n)}, v_h) \\ &\equiv \rho(u_h^{(n)})(z - v_h) + \rho(u_h^{(n)})(v_h). \end{aligned} \quad (33)$$

Here the first term is analogous to (32) with replacing the Galerkin solution  $u_h$  by the computed approximation  $u_h^{(n)}$ , and the second term can be considered as accounting for the deviation from the Galerkin orthogonality. Taking for  $v_h$  the computed approximation to the dual solution, i.e.  $v_h = z_h^{(n)}$ , and replacing the unknown exact dual solution  $z$  by its approximation obtained using the higher-order interpolation  $I_{2h}^{(2)}$  applied to  $z_h^{(n)}$ , i.e.

$$z - z_h^{(n)} \approx I_{2h}^{(2)} z_h^{(n)} - z_h^{(n)}, \quad (34)$$

we get

$$J(u - u_h^{(n)}) \approx \rho(u_h^{(n)})(I_{2h}^{(2)} z_h^{(n)} - z_h^{(n)}) + \rho(u_h^{(n)})(z_h^{(n)}). \quad (35)$$

The two terms on the right hand side account for the discretization and the algebraic error, respectively. The criterion balancing the discretization and the algebraic part of the error is then based on the requirement that the second term is significantly smaller than the first one. The practical implementations depend on the particular applications and the numerical methods used for discretization and algebraic computation; see [106], the later works [17, 28, 74, 75, 91, 100, 107, 108], and the recent instructive exposition in [109]. The DWR method should be given credit not only for its pioneering coupling of the discretization error and the algebraic error estimators, but also for its practical applications to solving linear as well as nonlinear problems, and for opening doors for further developments.

*Stopping criteria for Krylov subspace methods inspired by estimating the  $H^{-1}(\Omega)$  norm of the residual:* Krylov subspace methods, in combination with their *acceleration techniques* (commonly, but inaccurately, called preconditioning), belong to the very efficient tools for solving large-scale linear algebraic problems arising from the discretization of PDEs. As mentioned above, in case of  $\mathbf{a}(\cdot, \cdot)$  symmetric and coercive and thus  $\mathbf{A}$  symmetric positive definite, the CG method minimizes the  $\mathbf{A}$ -norm of the algebraic error over the Krylov subspaces generated by the powers of  $\mathbf{A}$  with respect to the initial residual.

Up to now, the majority of stopping criteria used in practical CG computations are based on the (relative) *Euclidean norm* of the algebraic residual  $\mathbf{r}^{(n)} = \mathbf{b} - \mathbf{A}\mathbf{u}_h^{(n)}$  (here  $\mathbf{u}_h^{(n)}$  denotes the approximation of  $\mathbf{u}_h$  computed at the  $n$ th CG iteration). Even without the mathematical modeling and numerical PDE context, this situation is most alarming. Already Hestenes and Stiefel warned in [72] against using the Euclidean residual norm as a base for CG stopping criteria, and they gave a hint on how the estimator for the energy norm of the error, i.e.

$$\|\mathbf{u}_h - \mathbf{u}_h^{(n)}\|_{\mathbf{A}} = \|\mathbf{r}^{(n)}\|_{\mathbf{A}^{-1}},$$

can be constructed using the computed quantities. Their recommendation was, however, overlooked for almost five decades.

A revived interest in estimating the (energy) norm of the error in CG and other iterative methods is due to Golub and his collaborators. Golub suggested (independently of [72]) to use for that purpose the family of (appropriately modified) Gauss-Christoffel quadrature approximations of the related quadratic formulas; see, e.g. [62, 63]. In [65] it was argued that since CG is based on short recurrences, any such estimate must take into account effects of rounding errors in CG computations. A few years later the story turned back to the original work of Hestenes and Stiefel [72]. The paper [123] highlighted the overlooked formulas presented by Hestenes and Stiefel and derived the estimator for  $\|\mathbf{r}^{(n)}\|_{\mathbf{A}^{-1}}$  using only the *local orthogonality* among the successive CG residuals and direction vectors. Since this local orthogonality is close to machine precision, the resulting estimate is numerically stable; for the proof see [123]. It should be pointed out, however, that while this holds for the lower bound on  $\|\mathbf{r}^{(n)}\|_{\mathbf{A}^{-1}}$ , which can be evaluated at almost no additional cost, a reliable upper bound can not be obtained without substantial a priori assumptions and/or an additional cost which may be significant. Details can be found in the survey paper [93], in the books [64, Chapter 12], [86, Chapter 5, in particular Sections 5.6 and 5.9], and in the original references presented there.

The energy norm of the Galerkin FEM discretization error in solving elliptic selfadjoint PDEs was coupled with the energy norm of the error in the corresponding algebraic computations in the so-called *cascadic CG method* by Deuffhard [51] published in 1994; see also, e.g. [118]. The algorithmic realisations of the cascadic CG do not take into account rounding errors and they could not use the results of estimating the algebraic energy norm of the error in CG published later. Therefore the idea is worth revisiting and further investigation.

A fundamental step in incorporating the state-of-the-art techniques of algebraic error estimation in CG (as well as other Krylov subspace methods) into the numerical PDE context is due to Arioli and his coworkers. They emphasized in [9] that the algebraic residual  $\mathbf{r}^{(n)}$  should be considered as the discrete counterpart of the functional residual which belongs to the dual of the space containing the solution; see (3) and the related discussion above. Therefore the algebraic stopping criteria should be based on the analogy of the dual norm of the

functional residual. For the Poisson model problem (1)–(2) this reduces to the algebraic energy norm of the error discussed above. The stopping criterion suggested in [5] then combines some *a priori* knowledge about the problem with the *a posteriori* error estimates; see also [64, Sections 12.3 and 12.7]. This approach has been extended to non-selfadjoint problems [7, 8] and it has motivated further ongoing investigations.

*BPX preconditioning and the residual a posteriori estimator without Galerkin orthogonality:* Harbrecht and Schneider [71] combined the idea of the standard residual a posteriori error estimator (see (25)–(26) above) with the multilevel Bramble, Pasciak and Xu preconditioning scheme (BPX) [32]. The infinite BPX scheme provides a frame for bounding the residual norm in the dual space  $H^{-1}(\Omega)$ . In practice the BPX scheme is truncated at a certain level. Neglecting the data oscillations, the resulting hierarchical estimator is composed of the discrete part  $BPX(\mathbf{r}^{(n)})^2$ , which can be evaluated using the BPX hierarchical scheme, and the standard residual a posteriori error estimator, giving

$$\eta_n \equiv \left( BPX(\mathbf{r}^{(n)})^2 + \sum_{\tau \in \mathcal{T}_h} h_\tau^2 \|\Delta u_h^{(n)} + f\|_{L^2(\tau)}^2 + \sum_{\varepsilon \in \mathcal{E}_h} h_\varepsilon \|\nabla u_h^{(n)} \cdot \mathbf{n}_\varepsilon\|_{L^2(\varepsilon)}^2 \right)^{1/2}. \quad (36)$$

The recent paper [71] recalls the earlier literature on the subject and investigates a rigorous background for this estimator.

*Estimators based on the equilibrated flux reconstruction:* Using a locally conservative cell-centered finite volume discretization, the a posteriori estimators of Vohralík mentioned above (cf. the end of Section 3) were in [76] extended in order to take into account the algebraic error. The resulting a posteriori error estimator is given as a sum of three quantities,

$$\eta_n \equiv \eta_{NC} + \eta_O + \eta_{AE}. \quad (37)$$

Here  $\eta_{NC}$ ,  $\eta_O$  and  $\eta_{AE}$  are called *nonconformity estimator*, *oscillation estimator* and *algebraic error estimator*, respectively; see [76, Theorem 5.2]. The nonconformity estimator indicates the departure of the approximate solution from the space  $H^1(\Omega)$ ; it depends on the approximation  $u_h^{(n)}$  of the solution  $u_h$  (and not only on the discretization error). The algebraic error estimator accounts for the error arising from the inexact solution of the algebraic system (11); its value is determined using the algebraic residual vector  $\mathbf{r}^{(n)}$ . Finally, the oscillation estimator measures the interpolation error in the right-hand side of the PDE (this value is significant only on coarse grids and for PDEs with highly varying coefficients). It is also shown in [76, Theorems 6.2 and 6.3] that the estimator (37) is locally and globally efficient (see Section 3) and therefore it is suitable for adaptive mesh refinement which takes into account the inaccurate algebraic computations. The results were successfully used for construction of stopping criteria in CG computations. Further work of Vohralík and his collaborators is outlined in [130]; the paper [57] extends the results from [76] to more general settings.

*Global convergence:* The standard a priori convergence theory for the FEM requires that  $h \rightarrow 0$ , i.e. that the mesh is refined everywhere, so that for each value of  $h$  the approximation error is of the required order of accuracy. This obviously does not hold in the context of the AFEM, where the main point is to avoid refining the mesh everywhere. Here the goal is to

show that the method is a contraction (for some appropriate norm of the error and/or error estimator) between two consecutive loops. Under the assumption of the *exact solution of the algebraic finite dimensional problem*, such a proof is given, e.g., in the paper of Morin, Nochetto, and Siebert [96]; see also the earlier work of Babuška and Vogelius [16] and of Dörfler [53]. In [96, p. 631] the authors conclude that “[a]ny prescribed error tolerance is thus achieved in a finite number of steps”, which is certainly true under the assumptions in their Theorems 3.1 and 3.11, and, in particular, under the assumption of exact algebraic computations; see also [26, 45, 82, 92, 97].

The fact that in practice we cannot compute the exact algebraic solution is addressed by Binev, Dahmen, and DeVore in [29]. They modify the method of [96] and prove that for the Poisson problem in two dimensions with piecewise linear finite elements their adaptive method has an optimal convergence rate with respect to the energy norm (and hence also the  $H^1$ -norm). One of the building blocks of their method is the application of preconditioned CG to the discretized problem. Their convergence proof of the AFEM requires that the (BPX-preconditioned) CG method gives an algebraic error norm below a given tolerance that depends on several parameters; see [29, Sections 3 and 8] for details.

Whether such tolerance can be met in practice depends, in general, on the *maximal attainable accuracy* of the iterative solver; see, e.g. [86, Section 5.9.3] and the references given there. This accuracy, in turn, depends on the properties of the problem, and also on the numerical stability of the solver itself. As an example we refer, e.g., to Example 6 in the book on iterative methods by Axelsson [10, Appendix A, pp. 608–609] and to the numerical experiments in [96]. This issue requires a complete rounding error analysis of the adaptive algorithms, a work that is still to be done. The existing approaches consider an inexact solution of algebraic problems in the sense of prematurely stopping the iterative computation (using an appropriate stopping criterion). Whether a maximal attainable accuracy has been reached is not considered an issue that affects the adaptive computations.

A highly recommendable paper by Stevenson [121] considers the Poisson model problem in two dimensions with piecewise linear finite elements. It presents a nice review of previous relevant work and it extends the approach in [96] by allowing an inexact solution of the discretized algebraic system. Its main result, presented in Theorem 6.3, holds under the assumption that the algebraic solver deviates from an ideal exact computation in a sufficiently small way. This assumption is mathematically specified, and it refers to a paper by Wu and Chen [136] on uniform convergence of multigrid V-cycle algorithms. The last paper assumes exact arithmetic and, in particular, it assumes that the operator on the coarsest grid is exactly invertible. Hence, as mentioned above, there still remains some work in order to account for all aspects of practical computations.

Assuming that a maximal attainable accuracy has not been approached, a result analogous to [45] has been proved in [6]. In that paper the algebraic problem is solved using the CG method and the energy norm of the finite dimensional error is estimated by the techniques described above. In particular, the global convergence result in [6] is based on the use of a well justified (although not strictly formally proved) upper bound for the energy norm of the algebraic error using the technique proposed in [87] for estimating an accurate lower bound of the smallest eigenvalue of the matrix  $\mathbf{A}$  in (11). A different approach which includes an adaptive stopping criterion for iterative solution of the algebraic problem has been used in [23, 24] for investigating the so-called quasi-optimal complexity of the AFEM; see also [25].

Finally, we want to mention that among the approaches to a posteriori error analysis which do not assume the exact solution of the discretized algebraic problem are the works of Wohlmuth and Hoppe [134], R de [113, 114, 115], Burstede and Kunoth [36, 37], Ma-day and Patera [88], and Patera and R nquist [102]. Indefinite and non-selfadjoint problems have been extensively addressed by Elman, Kay, Silvester, Simoncini, Wathen, and Wu; see, e.g. [55, 78, 119, 133, 135]. Lacking in space we can not describe their approaches and refer an interested reader to the original literature.

## 4.2 Results for eigenvalue problems

Minimizing the total errors (18)–(19) for eigenvalue problems is more complicated than minimizing (12) for boundary value problems where the CG method naturally minimizes the algebraic energy norm of the error. Even the definition of an appropriate (in the physical sense) norm to measure the error for the eigenvalue problem is not an easy task. We will briefly outline several recently investigated approaches.

The concept of a *functional backward error and condition number* introduced in [9] for boundary value problems were used in [94] for selfadjoint eigenvalue problems in order to analyze the continuous dependence of the inexact solution on the data, in particular to analyze the approximation error and the backward stability of the algebraic eigenvalue problem. This resulted in a combined residual a posteriori error estimator and a balanced AFEM algorithm, where the stopping criteria are based on the variant of the shift-invert Lanczos method introduced by Hetmaniuk and Lehoucq in [73]. A similar direction was considered by Gratton, Mouffe, and Toint [67] in the context of bound-constrained optimization; the ideas introduced there can be applied to the minimization of the Rayleigh-quotient in the case of eigenvalue computations.

Carstensen and Gedicke [42] combined an adaptive finite element scheme with an iterative algebraic eigenvalue solver and obtained a method of quasi-optimal computational complexity. Under the assumption that the iteration error  $\|u_h - u_h^{(n)}\|^2 + |\lambda_h - \lambda_h^{(n)}|$  for two consecutive AFEM steps is small in comparison with the size of the residual a posteriori error estimate, they showed the contraction property for the quasi-error up to higher-order terms. Checking the condition on the size of the iteration error is based on some heuristic arguments. A similar analysis of convergence and a quasi-optimality of the inexact inverse iteration coupled with adaptive finite element methods was presented by Zeiser [137].

The results above have been derived in the context of eigenvalue problems that usually are of the form (14) with  $\mathfrak{a}(\cdot, \cdot)$  symmetric and coercive. To deal with non-selfadjoint problems, one can follow Rannacher and Becker [28] and their DWR approach. Here duality techniques are used to estimate the error in the target quantities in terms of the weighted primal and dual residuals,

$$\rho(u_h, \lambda_h)(v) \equiv \mathfrak{a}(u_h, v) - \lambda_h(u_h, v), \quad (38)$$

$$\rho^*(u_h^*, \lambda_h^*)(v) \equiv \mathfrak{a}(v, u_h^*) - \lambda_h^*(v, u_h^*), \quad (39)$$

respectively. The resulting estimates can be written as

$$\lambda - \lambda_h^{(n)} \approx \frac{1}{1 - \sigma_n} \left( \eta_n + \eta_n^* + \eta_n^{(it)} \right), \quad (40)$$

where the primal and the dual eigenvalue residual estimators are given by

$$\eta_n \equiv \frac{1}{2} \rho(u_h^{(n)}, \lambda_h^{(n)}) (I_{2h}^{(2)} u_h^{*(n+1)} - u_h^{*(n)}), \quad (41)$$

$$\eta_n^* \equiv \frac{1}{2} \rho^*(u_h^{*(n)}, \lambda_h^{*(n)}) (I_{2h}^{(2)} u_h^{(n+1)} - u_h^{(n)}), \quad (42)$$

the term

$$\eta_n^{(it)} = \rho(u_h^{(n)}, \lambda_h^{(n)}) (u_h^{*(n)}) \quad (43)$$

represents an indicator for the iteration error, and the reminder term  $\sigma_n$  is assumed to be sufficiently small. The derivation is based on a perturbation argument and the application requires a careful monitoring of the computed quantities. For more details we refer to [110]. In practice the DWR method can be used in both boundary value and eigenvalue parts of various problems. An application to the stationary Navier-Stokes equations is given in [108], the studies in the context of the hydrodynamic stability analysis can be found in [75].

Finally, an algorithm based on a *homotopy method* which allows adaptivity in space, in the homotopy stepsize as well as in the stopping criteria for the iterative algebraic eigenvalue solvers is described in [43]; see also [60, 95].

## 5 Concluding remarks

This text gives a very brief introduction to the issues related to adaptive numerical solving of linear elliptic PDEs. Obviously, the work in the outlined directions has been extended to more general as well as to nonlinear problems. Many researchers are attracted by the fundamental character of the related applications, the difficulty of the mathematical problems, as well as the discretization and computational challenges (for an early account of the difficulties associated with the error control in the particularly intriguing area of computational fluid dynamics we refer to, e.g., [77]). We believe that this effort, with combination of expertise from fields such as mathematical modeling, mathematical and numerical PDE analysis and discretization, and matrix computations including numerical stability analysis, will lead to further remarkable results. Rigorous theoretical analysis complemented with soundly justified heuristics will bring adaptivity into the center of numerical computations.

**Acknowledgments.** The authors are grateful to Martin Vohralík, Vít Dolejší, Pavel Jiránek, Jan Papež, and three anonymous referees for correcting several errors in a previous version of the manuscript, for pointing out numerous important references, and for many valuable suggestions which improved the text.

Mario Arioli was supported by the EPSRC Grant EP/I013067/1. Jörg Liesen was supported by the Heisenberg-Programm of the Deutsche Forschungsgemeinschaft (DFG). Agnieszka Międlar was supported by the DFG Research Center MATHEON and by the Berlin Mathematical School. Zdeněk Strakoš was supported by the ERC-CZ project LL1202.

## References

- [1] R. A. Adams and J. J. F. Fournier. *Sobolev Spaces*, volume 140 of *Pure and Applied Mathematics*. Elsevier/Academic Press, Amsterdam, second edition, 2003.

- [2] M. Ainsworth and J. T. Oden. A posteriori error estimators for second order elliptic systems II. An optimal order process for calculating self-equilibrating fluxes. *Comput. Math. Appl.*, 26(9):75–87, 1993.
- [3] M. Ainsworth and J. T. Oden. *A Posteriori Error Estimation in Finite Element Analysis*. Pure and Applied Mathematics. Wiley-Interscience [John Wiley & Sons], New York, 2000.
- [4] M. Ainsworth and T. Vejchodský. Fully computable robust a posteriori error bounds for singularly perturbed reaction-diffusion problems. *Numer. Math.*, 119(2):219–243, 2011.
- [5] M. Arioli. A stopping criterion for the conjugate gradient algorithm in a finite element method framework. *Numer. Math.*, 97(1):1–24, 2004.
- [6] M. Arioli, E. H. Georgoulis, and D. Loghin. Convergence of inexact adaptive finite element solvers for elliptic problems. *SIAM J. Sci. Comput.*, to appear.
- [7] M. Arioli and D. Loghin. Stopping criteria for mixed finite element problems. *Electron. Trans. Numer. Anal.*, 29:178–192, 2007/08.
- [8] M. Arioli, D. Loghin, and A. J. Wathen. Stopping criteria for iterations in finite element methods. *Numer. Math.*, 99(3):381–410, 2005.
- [9] M. Arioli, E. Noulard, and A. Russo. Stopping criteria for iterative methods: applications to PDE's. *Calcolo*, 38(2):97–112, 2001.
- [10] O. Axelsson. *Iterative Solution Methods*. Cambridge University Press, Cambridge, 1994.
- [11] I. Babuška. Error-bounds for finite element method. *Numer. Math.*, 16:322–333, 1970/1971.
- [12] I. Babuška and J. E. Osborn. Finite element-Galerkin approximation of the eigenvalues and eigenvectors of selfadjoint problems. *Math. Comp.*, 52(186):275–297, 1989.
- [13] I. Babuška and J. E. Osborn. *Eigenvalue Problems. Handbook of Numerical Analysis Vol. II*. North Holland, Amsterdam, 1991.
- [14] I. Babuška and W. C. Rheinboldt. Error estimates for adaptive finite element computations. *SIAM J. Numer. Anal.*, 15(4):736–754, 1978.
- [15] I. Babuška and T. Strouboulis. *The Finite Element Method and Its Reliability*. Numerical Mathematics and Scientific Computation. Oxford University Press, New York, 2001.
- [16] I. Babuška and M. Vogelius. Feedback and adaptive finite element solution of one-dimensional boundary value problems. *Numer. Math.*, 44(1):75–102, 1984.
- [17] W. Bangerth and R. Rannacher. *Adaptive Finite Element Methods for Differential Equations*. Lectures in Mathematics ETH Zürich. Birkhäuser Verlag, Basel, 2003.
- [18] R. E. Bank and L. Ridgway Scott. On the conditioning of finite element equations with highly refined meshes. *SIAM J. Numer. Anal.*, 26(6):1383–1394.
- [19] R. E. Bank and R. K. Smith. A posteriori error estimates based on hierarchical bases. *SIAM J. Numer. Anal.*, 30(4):921–935, 1993.
- [20] R. E. Bank and A. Weiser. Some a posteriori error estimators for elliptic partial differential equations. *Math. Comp.*, 44(170):283–301, 1985.
- [21] R. Becker. An adaptive finite element method for the Stokes equation including control of the iteration error. In H. G. Bock et al., editor, *ENUMATH 97 (Heidelberg)*, pages 609–620. World Sci. Publ., Singapore, 1998.
- [22] R. Becker, C. Johnson, and R. Rannacher. Adaptive error control for multigrid finite element methods. *Computing*, 55(4):271–288, 1995.
- [23] R. Becker and S. Mao. An optimally convergent adaptive mixed finite element method. *Numer. Math.*, 111(1):35–54, 2008.
- [24] R. Becker and S. Mao. Convergence and quasi-optimal complexity of a simple adaptive finite element method. *M2AN Math. Model. Numer. Anal.*, 43(6):1203–1219, 2009.
- [25] R. Becker, S. Mao, and Z. Shi. A convergent nonconforming adaptive finite element method with quasi-optimal complexity. *SIAM J. Numer. Anal.*, 47(6):4639–4659, 2010.
- [26] R. Becker, S. Mao, and Z.-C. Shi. A convergent adaptive finite element method with optimal complexity. *Electron. Trans. Numer. Anal.*, 30:291–304, 2008.
- [27] R. Becker and R. Rannacher. Weighted a posteriori error control in FE methods. In H. G. Bock et al., editor, *ENUMATH 97 (Heidelberg)*, pages 621–637. World Sci. Publ., Singapore, 1998.

- [28] R. Becker and R. Rannacher. An optimal control approach to a posteriori error estimation in finite element methods. *Acta Numer.*, 10:1–102, 2001.
- [29] P. Binev, W. Dahmen, and R. DeVore. Adaptive finite element methods with convergence rates. *Numer. Math.*, 97(2):219–268, 2004.
- [30] D. Boffi. Finite element approximation of eigenvalue problems. *Acta Numer.*, 19:1–120, 2010.
- [31] D. Boffi, F. Gardini, and L. Gastaldi. Some remarks on eigenvalue approximation by finite elements. In *Frontiers in Numerical Analysis – Durham 2010*, volume 85 of *Springer Lecture Notes in Computational Science and Engineering*, pages 1–77. Springer-Verlag, 2012.
- [32] J. Bramble, J. Pasciak, and J. Xu. Parallel multilevel preconditioners. *Math. Comp.*, 55(191):1–22, 1990.
- [33] S. C. Brenner and C. Carstensen. Finite Element Methods. In E. Stein, R. de Borst, and T. J. R. Huges, editors, *Encyclopedia of Computational Mechanics, Vol. I*, pages 73–114. John Wiley and Sons Inc., New York, 2004.
- [34] S. C. Brenner and L. R. Scott. *The Mathematical Theory of Finite Element Methods*, volume 15 of *Texts in Applied Mathematics*. Springer, New York, third edition, 2008.
- [35] H. Brezis. *Functional Analysis, Sobolev Spaces and Partial Differential Equations*. Universitext. Springer, New York, 2011.
- [36] C. Burstedde and A. Kunoth. Fast iterative solution of elliptic control problems in wavelet discretization. *J. Comput. Appl. Math.*, 196(1):299–319, 2006.
- [37] C. Burstedde and A. Kunoth. A wavelet-based nested iteration-inexact conjugate gradient algorithm for adaptively solving elliptic PDEs. *Numer. Algorithms*, 48(1-3):161–188, 2008.
- [38] C. Carstensen. Some remarks on the history and future of averaging techniques in a posteriori finite element error analysis. *ZAMM Z. Angew. Math. Mech.*, 84(1):3–21, 2004.
- [39] C. Carstensen and S. A. Funken. Constants in Clément-interpolation error and residual based a posteriori error estimates in finite element methods. *East-West J. Numer. Math.*, 8(3):153–175, 2000.
- [40] C. Carstensen and S. A. Funken. Fully reliable localized error control in the FEM. *SIAM J. Sci. Comput.*, 21(4):1465–1484, 2000.
- [41] C. Carstensen and J. Gedicke. An oscillation-free adaptive FEM for symmetric eigenvalue problems. *Numer. Math.*, 118(3):401–427, 2011.
- [42] C. Carstensen and J. Gedicke. An adaptive finite element eigenvalue solver of asymptotic quasi-optimal computational complexity. *SIAM J. Numer. Anal.*, 50(3):1029–1057, 2012.
- [43] C. Carstensen, J. Gedicke, V. Mehrmann, and A. Międlar. An adaptive homotopy approach for non-selfadjoint eigenvalue problems. *Numer. Math.*, 119(3):557–583, 2011.
- [44] C. Carstensen and C. Merdon. Estimator competition for Poisson problems. *J. Comput. Math.*, 28(3):309–330, 2010.
- [45] J. M. Cascon, C. Kreuzer, R. H. Nochetto, and K. G. Siebert. Quasi-optimal convergence rate for an adaptive finite element method. *SIAM J. Numer. Anal.*, 46(5):2524–2550, 2008.
- [46] J. Céa. Approximation variationnelle des problèmes aux limites. *Ann. Inst. Fourier (Grenoble)*, 14(fasc. 2):345–444, 1964.
- [47] F. Chatelin. *Spectral Approximation of Linear Operators*, volume 65 of *Classics in Applied Mathematics*. Society for Industrial and Applied Mathematics (SIAM), Philadelphia, PA, 2011. Reprint of the 1983 original (Academic Press, New York).
- [48] I. Cheddadi, R. Fučík, M. I. Prieto, and Martin Vohralík. Computable a posteriori error estimates in the finite element method based on its local conservativity: Improvements using local minimization. In *ESAIM: Proceedings*, volume 24, pages 77–96. 2008.
- [49] Z. Chen. *Finite Element Methods and Their Applications*. Scientific Computation. Springer-Verlag, Berlin, 2005.
- [50] P. G. Ciarlet. *The Finite Element Method for Elliptic Problems*, volume 40 of *Classics in Applied Mathematics*. Society for Industrial and Applied Mathematics (SIAM), Philadelphia, PA, 2002. Reprint of the 1978 original (North-Holland, Amsterdam).

- [51] P. Deuffhard. Cascadic conjugate gradient methods for elliptic partial differential equations: algorithm and numerical results. In *Domain Decomposition Methods in Scientific and Engineering Computing (University Park, PA, 1993)*, volume 180 of *Contemp. Math.*, pages 29–42. Amer. Math. Soc., Providence, RI, 1994.
- [52] P. Deuffhard, P. Leinen, and H. Yserentant. Concepts of an adaptive hierarchical finite element code. *IMPACT Comp. Sci. Eng.*, 1(1):3–35, 1989.
- [53] W. Dörfler. A convergent adaptive algorithm for Poisson’s equation. *SIAM J. Numer. Anal.*, 33(3):1106–1124, 1996.
- [54] R. G. Durán, C. Padra, and R. Rodríguez. A posteriori error estimates for the finite element approximation of eigenvalue problems. *Math. Models Methods Appl. Sci.*, 13(8):1219–1229, 2003.
- [55] H. Elman, D. Silvester, and A. Wathen. *Finite Elements and Fast Iterative Solvers with Applications in Incompressible Fluid Dynamics*. Numerical Mathematics and Scientific Computation. Oxford University Press, New York, 2005.
- [56] K. Eriksson, D. Estep, P. Hansbo, and C. Johnson. Introduction to adaptive methods for differential equations. *Acta Numer.*, pages 105–158, 1995.
- [57] A. Ern and M. Vohralík. Adaptive inexact Newton methods with a posteriori stopping criteria for nonlinear diffusion PDEs. *Submitted for publication*, 2012.
- [58] L. C. Evans. *Partial Differential Equations*, volume 19 of *Graduate Studies in Mathematics*. American Mathematical Society, Providence, RI, second edition, 2010.
- [59] S. Ferraz-Leite, C. Ortner, and D. Praetorius. Convergence of simple adaptive Galerkin schemes based on  $h - h/2$  error estimators. *Numer. Math.*, 116(2):291–316, 2010.
- [60] J. Gedicke and C. Carstensen. A posteriori error estimators for non-symmetric eigenvalue problems. Preprint 659, DFG Research Center MATHEON, Berlin, 2009.
- [61] M. S. Gockenbach. *Understanding and Implementing the Finite Element Method*. Society for Industrial and Applied Mathematics (SIAM), Philadelphia, PA, 2006.
- [62] G. H. Golub and G. Meurant. Matrices, moments and quadrature. In *Numerical Analysis 1993 (Dundee, 1993)*, volume 303 of *Pitman Res. Notes Math. Ser.*, pages 105–156. Longman Sci. Tech., Harlow, 1994.
- [63] G. H. Golub and G. Meurant. Matrices, moments and quadrature II; How to compute the norm of the error in iterative methods. *BIT*, 37(3):687–705, 1997.
- [64] G. H. Golub and G. Meurant. *Matrices, Moments and Quadrature with Applications*. Princeton Series in Applied Mathematics. Princeton University Press, Princeton, NJ, 2010.
- [65] G. H. Golub and Z. Strakoš. Estimates in quadratic formulas. *Numer. Algorithms*, 8(2-4):241–268, 1994.
- [66] T. Grätsch and K.-J. Bathe. A posteriori error estimation techniques in practical finite element analysis. *Comput. & Structures*, 83(4-5):235–265, 2005.
- [67] S. Gratton, M. Mouffe, and P. L. Toint. Stopping rules and backward error analysis for bound-constrained optimization. *Numer. Math.*, 119(1):163–187, 2011.
- [68] P. Grisvard. *Elliptic Problems in Nonsmooth Domains*, volume 24 of *Monographs and Studies in Mathematics*. Pitman (Advanced Publishing Program), Boston, MA, 1985.
- [69] W. Hackbusch. *Elliptic Differential Equations*, volume 18 of *Springer Series in Computational Mathematics*. Springer-Verlag, Berlin, 1992. Translated from the author’s revision of the 1986 German original by Regine Fadiman and Patrick D. F. Ion.
- [70] A. Hannukainen, R. Stenberg, and M. Vohralík. A unified framework for a posteriori error estimation for the Stokes problem. *Numer. Math.*, 122(4):725–769, 2012.
- [71] H. Harbrecht and R. Schneider. On error estimation in finite element methods without having Galerkin orthogonality. Preprint 457, Berichtreihe des SFB 611, Universität Bonn, 2009.
- [72] M. R. Hestenes and E. Stiefel. Methods of conjugate gradients for solving linear systems. *J. Research Nat. Bur. Standards*, 49:409–436, 1952.
- [73] U. L. Hetmaniuk and R. B. Lehoucq. Uniform accuracy of eigenpairs from a shift-invert Lanczos method. *SIAM J. Matrix Anal. Appl.*, 28(4):927–948, 2006.

- [74] V. Heuveline and R. Rannacher. A posteriori error control for finite element approximations of elliptic eigenvalue problems. *Adv. Comp. Math.*, 15(1-4):107–138, 2001.
- [75] V. Heuveline and R. Rannacher. Adaptive FEM for eigenvalue problems with application in hydrodynamic stability analysis. In *Advances in Numerical Mathematics*, Proc. Int. Conf., Sept. 16-17, 2005, Moscow. Institute of Numerical Mathematics, RAS, 2006.
- [76] P. Jiránek, Z. Strakoš, and M. Vohralík. A posteriori error estimates including algebraic error and stopping criteria for iterative solvers. *SIAM J. Sci. Comput.*, 32(3):1567–1590, 2010.
- [77] C. Johnson, R. Rannacher, and M. Boman. Numerics and hydrodynamic stability: toward error control in computational fluid dynamics. *SIAM J. Numer. Anal.*, 32(4):1058–1079, 1995.
- [78] D. Kay and D. Silvester. The reliability of local error estimators for convection-diffusion equations. *IMA J. Numer. Anal.*, 21(1):107–122, 2001.
- [79] R. C. Kirby. From functional analysis to iterative methods. *SIAM Rev.*, 52(2):269–293, 2010.
- [80] A. V. Knyazev. New estimates for Ritz vectors. *Math. Comp.*, 66(219):985–995, 1997.
- [81] A. V. Knyazev and J. E. Osborn. New a priori FEM error estimates for eigenvalues. *SIAM J. Numer. Anal.*, 43(6):2647–2667, 2006.
- [82] C. Kreuzer and K. G. Siebert. Decay rates of adaptive finite elements with Dörfler marking. *Numer. Math.*, 117(4):679–716, 2011.
- [83] P. Ladevèze. *Comparaison de Modèles de Milieux Continus*. PhD thesis, Université Pierre et Marie Curie (Paris 6), 1975.
- [84] M. G. Larson. A posteriori and a priori error analysis for finite element approximations of self-adjoint elliptic eigenvalue problems. *SIAM J. Numer. Anal.*, 38(2):608–625, 2000.
- [85] P. D. Lax and A. N. Milgram. Parabolic equations. In *Contributions to the Theory of Partial Differential Equations*, Annals of Mathematics Studies, no. 33, pages 167–190. Princeton University Press, Princeton, N. J., 1954.
- [86] J. Liesen and Z. Strakoš. *Krylov Subspace Methods. Principles and Analysis*. Oxford University Press, Oxford, 2012.
- [87] D. Loghin. Eigenvalue estimation by domain decomposition. *Submitted for publication*, 2012.
- [88] Y. Maday and A. T. Patera. Numerical analysis of a posteriori finite element bounds for linear functional outputs. *Math. Models Methods Appl. Sci.*, 10(5):785–799, 2000.
- [89] D. Mao, L. Shen, and A. Zhou. Adaptive finite element algorithms for eigenvalue problems based on local averaging type a posteriori error estimates. *Adv. Comput. Math.*, 25(1-3):135–160, 2006.
- [90] V. Mehrmann and A. Międlar. Adaptive computation of smallest eigenvalues of self-adjoint elliptic partial differential equations. *Numer. Linear Algebra Appl.*, 18(3):387–409, 2011.
- [91] D. Meidner, R. Rannacher, and J. Vihharev. Goal-oriented error control of the iterative solution of finite element equations. *J. Numer. Math.*, 17(2):143–172, 2009.
- [92] K. Mekchay and R. H. Nochetto. Convergence of adaptive finite element methods for general second order linear elliptic PDEs. *SIAM J. Numer. Anal.*, 43(5):1803–1827, 2005.
- [93] G. Meurant and Z. Strakoš. The Lanczos and conjugate gradient algorithms in finite precision arithmetic. *Acta Numer.*, 15:471–542, 2006.
- [94] A. Międlar. Functional perturbation results and the balanced AFEM algorithm for self-adjoint PDE eigenvalue problems. Preprint 817, DFG Research Center MATHEON, Berlin, 2011.
- [95] A. Międlar. *Inexact Adaptive Finite Element Methods for Elliptic PDE Eigenvalue Problems*. PhD thesis, Technische Universität Berlin, 2011.
- [96] P. Morin, R. H. Nochetto, and K. G. Siebert. Convergence of adaptive finite element methods. *SIAM Rev.*, 44(4):631–658, 2002. Revised reprint of “Data oscillation and convergence of adaptive FEM” [SIAM J. Numer. Anal. 38 (2000), no. 2, 466–488].
- [97] P. Morin, R. H. Nochetto, and K. G. Siebert. Local problems on stars: a posteriori error estimators, convergence, and performance. *Math. Comp.*, 72(243):1067–1097, 2003.
- [98] K. Neymeyr. A posteriori error estimation for elliptic eigenproblems. *Numer. Linear Algebra Appl.*, 9(4):263–279, 2002.

- [99] R. H. Nochetto, K. G. Siebert, and A. Veiser. Theory of adaptive finite element methods: an introduction. In *Multiscale, Nonlinear and Adaptive Approximation*, pages 409–542. Springer, Berlin, 2009.
- [100] J. T. Oden and S. Prudhomme. Goal-oriented error estimation and adaptivity for the finite element method. *Comput. Math. Appl.*, 41(5-6):735–756, 2001.
- [101] J. Papež, J. Liesen, and Z. Strakoš. On distribution of the discretization and algebraic error in 1D Poisson model problem. Preprint 2012/03, MORE Research Project, 2012.
- [102] A. T. Patera and E. M. Rønquist. A general output bound result: application to discretization and iteration error estimation and control. *Math. Models Methods Appl. Sci.*, 11(4):685–712, 2001.
- [103] M. Picasso. A stopping criterion for the conjugate gradient algorithm in the framework of anisotropic adaptive finite elements. *Commun. Numer. Meth. Engng.*, 25(4):339–355, 2009.
- [104] W. Prager and J. L. Synge. Approximations in elasticity based on the concept of function space. *Quart. Appl. Math.*, 5:241–269, 1947.
- [105] A. Quarteroni and A. Valli. *Numerical Approximation of Partial Differential Equations*. Springer Series in Computational Mathematics. Springer-Verlag, Berlin, 2008.
- [106] R. Rannacher. Error control in finite element computations. An introduction to error estimation and mesh-size adaptation. In *Error Control and Adaptivity in Scientific Computing (Antalya, 1998)*, volume 536 of *NATO Sci. Ser. C Math. Phys. Sci.*, pages 247–278. Kluwer Acad. Publ., Dordrecht, 1999.
- [107] R. Rannacher. Adaptive finite element methods for partial differential equations. In *Proceedings of the International Congress of Mathematicians, Vol. III (Beijing, 2002)*, pages 717–726, Beijing, 2002. Higher Ed. Press.
- [108] R. Rannacher. Adaptive finite element discretization of flow problems for goal-oriented model reduction. In *Computational Fluid Dynamics Review 2010*, pages 51–70. World Sci. Publ., Hackensack, NJ, 2010.
- [109] R. Rannacher. A short course on numerical simulation of viscous flow: discretization, optimization and stability analysis. *Discrete and Continuous Dynamical Systems Series S*, 5(6):1147–1194, 2012.
- [110] R. Rannacher, A. Westenberger, and W. Wollner. Adaptive finite element solution of eigenvalue problems: balancing of discretization and iteration error. *J. Numer. Math.*, 18(4):303–327, 2010.
- [111] P.-A. Raviart and J.-M. Thomas. *Introduction à l'Analyse Numérique des Équations aux Dérivées Partielles*. Collection Mathématiques Appliquées pour la Maîtrise. Masson, Paris, 1983.
- [112] S. I. Repin. *A Posteriori Estimates for Partial Differential Equations*, volume 4 of *Radon Series on Computational and Applied Mathematics*. Walter de Gruyter GmbH & Co. KG, Berlin, 2008.
- [113] U. Rüde. Fully adaptive multigrid methods. *SIAM J. Numer. Anal.*, 30(1):230–248, 1993.
- [114] U. Rüde. Error estimates based on stable splittings. In *Domain Decomposition Methods in Scientific and Engineering Computing (University Park, PA, 1993)*, volume 180 of *Contemp. Math.*, pages 111–118. Amer. Math. Soc., Providence, RI, 1994.
- [115] U. Rüde. On the multilevel adaptive iterative method. *SIAM J. Sci. Comput.*, 15(3):577–586, 1994.
- [116] S. Sauter. Finite Elements for Elliptic Eigenvalue Problems: Lecture Notes for the Zürich Summerschool 2008. Preprint 12–08, Institut für Mathematik, Universität Zürich, 2008. [http://www.math.uzh.ch/compmath/fileadmin/math/preprints/12\\_08.pdf](http://www.math.uzh.ch/compmath/fileadmin/math/preprints/12_08.pdf).
- [117] K. Segeth. A review of some a posteriori error estimates for adaptive finite element methods. *Math. Comput. Simulation*, 80(8):1589–1600, 2010.
- [118] V. Shaidurov and L. Tobiska. The convergence of the cascadic conjugate-gradient method applied to elliptic problems in domains with re-entrant corners. *Math. Comp.*, 69(230):501–520, 2000.
- [119] D. J. Silvester and V. Simoncini. An optimal iterative solver for symmetric indefinite systems stemming from mixed approximation. *ACM Trans. Math. Software*, 37(4):Art. 42, 22, 2011.
- [120] P. Šolín. *Partial Differential Equations and the Finite Element Method*. Pure and Applied Mathematics (New York). Wiley-Interscience [John Wiley & Sons], Hoboken, NJ, 2006.

- [121] R. Stevenson. Optimality of a standard adaptive finite element method. *Found. Comput. Math.*, 7(2):245–269, 2007.
- [122] Z. Strakoš and J. Liesen. On numerical stability in large scale linear algebraic computations. *ZAMM Z. Angew. Math. Mech.*, 85(5):307–325, 2005.
- [123] Z. Strakoš and P. Tichý. On error estimation in the conjugate gradient method and why it works in finite precision computations. *Electron. Trans. Numer. Anal.*, 13:56–80, 2002.
- [124] G. Strang and G. J. Fix. *An Analysis of the Finite Element Method*. Prentice-Hall Inc., Englewood Cliffs, N. J., 1973. Prentice-Hall Series in Automatic Computation.
- [125] J. L. Synge. *The Hypercircle in Mathematical Physics: A Method for the Approximate Solution of Boundary Value Problems*. Cambridge University Press, New York, 1957.
- [126] A. Veiser and R. Verfürth. Explicit upper bounds for dual norms of residuals. *SIAM J. Numer. Anal.*, 47(3):2387–2405, 2009.
- [127] T. Vejchodský. Complementarity based a posteriori error estimates and their properties. *Math. Comput. Simulation*, 82(10):2033–2046, 2012.
- [128] R. Verfürth. *A Review of A Posteriori Error Estimation and Adaptive Mesh-Refinement Techniques*. Wiley and Teubner, New York, Stuttgart, 1996.
- [129] M. Vohralík. Residual flux-based a posteriori error estimates for finite volume and related locally conservative methods. *Numer. Math.*, 111(1):121–158, 2008.
- [130] M. Vohralík. *A Posteriori Error Estimates, Stopping Criteria, and Inexpensive Implementations for Error Control and Efficiency in Numerical Simulations*. Habilitation Thesis, Université Pierre et Marie Curie, 2010. [http://www.ann.jussieu.fr/~vohralik/Files/HdR\\_en.pdf](http://www.ann.jussieu.fr/~vohralik/Files/HdR_en.pdf).
- [131] M. Vohralík. *A posteriori error estimates for efficiency and error control in numerical simulations. Lecture Notes*, 2012. <http://www.ann.jussieu.fr/~vohralik/Enseig/APost/grades.pdf>.
- [132] T. F. Walsh, G. M. Reese, and U. L. Hetmaniuk. Explicit a posteriori error estimates for eigenvalue analysis of heterogeneous elastic structures. *Comput. Methods Appl. Mech. Engrg.*, 196(37–40):3614–3623, 2007.
- [133] A. Wathen. Preconditioning and convergence in the right norm. *Int. J. Comput. Math.*, 84(8):1199–1209, 2007.
- [134] B. I. Wohlmuth and R. H. W. Hoppe. A comparison of a posteriori error estimators for mixed finite element discretizations by Raviart-Thomas elements. *Math. Comp.*, 68(228):1347–1378, 1999.
- [135] C.-T. Wu and H. C. Elman. Analysis and comparison of geometric and algebraic multigrid for convection-diffusion equations. *SIAM J. Sci. Comput.*, 28(6):2208–2228, 2006.
- [136] H. Wu and Z. Chen. Uniform convergence of multigrid V-cycle on adaptively refined finite element meshes for second order elliptic problems. *Sci. China Ser. A*, 49(10):1405–1429, 2006.
- [137] A. Zeiser. On the optimality of the inexact inverse iteration coupled with adaptive finite element methods. Preprint 57, DFG-SPP 1324, 2010.
- [138] O. C. Zienkiewicz and J. Zhu. A simple error estimator and adaptive procedure for practical engineering analysis. *Internat. J. Numer. Methods Engrg.*, 24(2):337–357, 1987.